ESSECIPLAST®

PRESTIGE

PRESTIGE è un rivestimento in PVC eterogeneo in piastrelle 620*620 mm, con bordi bisellati, dallo spessore totale di 5 mm, con una struttura semirigida in PVC rinforzato con fibre di vetro, un film di decoro e con uno strato di usura poliuretanico superficiale flessibile di 0,7 mm per alto traffico quindi idoneo ad ambienti commerciali, che offre il massimo comfort e riduce il suono del camminamento. Lo strato inferiore presenta un supporto antislip per facilitare l'installazione.

PRESTIGE è un pavimento autoposante, resistente all'uso commerciale con classe di reazione al fuoco Bfl-s1 secondo la EN 13501-1 e resistenza allo scivolamento R10 secondo la DIN 51130.

PRESTIGE is a heterogeneous PVC cladding in 914*914 mm tiles, with bevelled edges, with a total thickness of 5 mm, with a semi-rigid structure in glass fiber reinforced PVC, a decorative film and with a flexible surface polyurethane wear layer of 0.7 mm for high traffic therefore suitable for commercial environments, that offers maximum comfort and reduces the sound of walking. The bottom layer features an anti-slip backing for ease of installation.

PRESTIGE is a loose-lay floor, resistant to commercial use with fire reaction class Bfl-s1 according to EN 13501-1 and slip resistance R10 according to DIN 51130.